

## OPUS

Opus 5 1/2" Shower Head, Arm and Flange

OP71SH



SHOWN IN OPUS 5 1/2" SHOWER HEAD, ARM AND FLANGE| OP71SH

### TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray  
Diameter of Head: 140 mm  
Escutcheon Primary Material: Brass  
Fittings Hole Diameter: 35 mm  
Depth / Width: 305 mm  
Height: 165 mm  
Inlet Connection Size: 1/2"  
Inlet Connection Type: Male G/BSPP  
Integrated Diverter: N  
Length: 152 mm  
Pivot: N  
Primary Material: Brass  
Restricted Maximum Flow Rate: 9.5 liters/min  
Suggested Application: Bath  
Water Pressure Maximum: 6.0 bar  
Water Pressure Minimum: 1.5 bar  
Water Pressure Recommended: 3.0 bar

### INSPIRATION

Opus incorporates a range of sophisticated aesthetic notes, with graceful curves that create a jewel-like refinement.

### CODES & STANDARDS

Code # : ASME A112.18.1, CSA B125, IAPMO, State of MA

### PRODUCT FEATURES

Brass material is used for trim and valve component parts.

The manufacturing process encompasses casting, turning, stamping, hand-fitting and hand polishing.

Eased curves and reflective forms carry the message of cleanliness and clarity.

An extensive range of fittings, fixture and accessory options for the lavatory, shower, bathtub.

Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

# WATERWORKS

## OPUS

Opus 5 1/2" Shower Head, Arm and Flange

## OP71SH

