

## REGULATOR

RGXT50

Regulator Exposed Deck Mounted Tub Filler with Handshower and Black Lever Handles



SHOWN IN REGULATOR EXPOSED DECK MOUNTED TUB FILLER WITH HANDSHOWER AND BLACK LEVER HANDLES | RGXT50

### TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed  
 Deck Thickness Maximum: 2 1/2"  
 Deck Thickness Minimum: 1/4"  
 Depth/Width: 11 13/16"  
 Fittings Hole Diameter: 1 3/8"  
 Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92  
 Handle Turn Angle: Quarter Turn  
 Handshower Spray Hose Length: 59"  
 Height: 19 7/8"  
 Inlet Connection Size: 3/4"  
 Inlet Connection Type: Male BSPP  
 Inlet Supply Spread Maximum: 8"  
 Inlet Supply Spread Minimum: 8"  
 Integrated Diverter: Y  
 Integrated Spray: Y  
 Length: 17 3/16"  
 Primary Material: Brass  
 Suggested Application: Bath  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

### CODES & STANDARDS

### PRODUCT FEATURES

Matte Black Lever Handle

Includes Required Unions for Mounting

Exposed Tub Fillers feature a unique shut-off and diverter valve inside the decorative valve body. Handshower features anti-drip technology.

Stocked in Nickel, Chrome and Unlacquered Brass

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

### CERTIFICATIONS

### PRODUCT (NOTES)

## REGULATOR

RGXT50

Regulator Exposed Deck Mounted Tub Filler with Handshower and Black Lever Handles

