

ISLA

ISLS65

Isla Wall Mounted Lavatory Faucet with Metal Geode Handles



SHOWN IN ISLA WALL MOUNTED LAVATORY FAUCET WITH METAL GEODE HANDLES | ISLS65

TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed Spray
 Depth/Width: 9"
 Drain Depth Maximum: 2 5/8"
 Drain Depth Minimum: 3/8"
 Drain Hole Diameter: 1 3/4"
 Drain Style: Push Touch
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 1 3/8"
 Handle Spread Maximum: 8"
 Handle Spread Minimum: 8"
 Handle Turn Angle: Quarter Turn
 Height: 3 1/8"
 Inlet Connection Size: 3/4"
 Inlet Connection Type: Female NPT
 Inlet Supply Spread Maximum: 8"
 Inlet Supply Spread Minimum: 8"
 Length: 10 5/8"
 Number Of Holes: Three Hole
 Restricted Maximum Flow Rate: 1.2 gpm
 Spout Swivel: N
 Suggested Application: Bath
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Pure, timeless, unique and versatile - sculptural organic forms meet advanced engineering in this inspiring collection of fittings, hardware and accessories.

CODES & STANDARDS

Code # ISLS65: CEC

PRODUCT FEATURES

Features faceted Geode Handles

Includes European size push touch drain

Requires rough valve, sold separately: GULV27 (US) / GU27LV (UK)

Stocked in Nickel, Burnished Nickel, and Burnished Brass

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

ISLA

ISLS65

Isla Wall Mounted Lavatory Faucet with Metal Geode
Handles

