

## REGULATOR

RGXT70

Regulator Exposed Floor Mounted Tub Filler with Handshower and Black Lever Handles



SHOWN IN REGULATOR EXPOSED FLOOR MOUNTED TUB FILLER WITH HANDSHOWER AND BLACK LEVER HANDLES | RGXT70

### TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed  
Depth/Width: 11 13/16"  
Fittings Hole Diameter: 1 3/8"  
Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92  
Handle Turn Angle: Quarter Turn  
Handshower Spray Hose Length: 59"  
Height: 36"  
Inlet Connection Size: 3/4"  
Inlet Connection Type: Sweat  
Inlet Supply Spread Maximum: 8"  
Inlet Supply Spread Minimum: 8"  
Integrated Diverter: Y  
Integrated Spray: Y  
Length: 17 3/16"  
Primary Material: Brass  
Suggested Application: Bath  
Water Pressure Maximum: 85.0 psi  
Water Pressure Minimum: 20.0 psi  
Water Pressure Recommended: 45.0 psi

### INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

### CODES & STANDARDS

### PRODUCT FEATURES

Matte Black Lever Handle

Includes Required Unions for Mounting

Exposed Tub Fillers feature a unique shut-off and diverter valve inside the decorative valve body. Handshower features anti-drip technology.

Stocked in Nickel, Chrome and Unlacquered Brass

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details

### CERTIFICATIONS

### PRODUCT (NOTES)

## REGULATOR

RGXT70

Regulator Exposed Floor Mounted Tub Filler with  
Handshower and Black Lever Handles

