

.25

.25 Thermostatic Valve

GUTH78



TECHNICAL DETAILS

Fittings Hole Diameter: 7"
 Depth / Width: 3 1/2"
 Height: 5 1/4"
 Inlet Connection Size: 3/4"
 Inlet Connection Type: Female NPT
 Length: 6 1/2"
 Outlet Connection Size: 3/4"
 Outlet Connection Type: Female NPT
 Primary Material: Brass
 Suggested Application: Bath
 Valve Material: Bi-metal strip
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful.

CODES & STANDARDS

Code # GUSV78: ASME A112.18.1 / CSA B125.1, State of Ma

PRODUCT FEATURES


- Built in Anti-scald protection.
- Unrestricted maximum flow of 15.7 gallons per minute (GPM) at 45 psi
- Designed exclusively for the .25 Thermostatic Control Valve Trim
- Integrated check valves guarantee there is no crossover of hot or cold water.




.25

.25 Thermostatic Valve


GUTH78



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"