WATERWORKS

ELSA ELXT52

Elsa Exposed Tub Filler with Metal Cross Handles and Handshower and Metal Lever Diverter



TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray Diameter of Head: 2"
Diameter of Legs / Tubes: 1 1/4"
Escutcheon Primary Material: brass Fittings Hole Diameter: 1 1/4"
Flow Restriction Options: 2.0, 1.75, 1.5, 0.92
Handle Spread Maximum: 5.9"

Handle Spread Minimum: 5.9" Depth / Width: 7"

Height: 13"
Inlet Connection Size: 1/2"
Inlet Connection Type: Male NPT
Inlet Supply Spread Maximum: 6.3"
Inlet Supply Spread Minimum: 5 1/2"
Integrated Diverter: Y

Length: 9" Pivot: N

Primary Material: Brass

Restricted Maximum Flow Rate: 2.5 gpm

Spout Reach: 6 1/4" Spout Swivel: N

Suggested Application: Bath Valve Material: ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN CHROME

INSPIRATION

An updated 1930's design that is curvaceous and bold; Elsa conveys charm, warmth and a touch of whimsy.

CODES & STANDARDS

Code # ELTU52: ASME A112.18.1, CSA B125, IAPMO, State of MA $\,$

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

The manufacturing processÁMA encompassesÁMA casting, turning, hand-fitting and hand polishing.

The smooth, sculptural contours and simplified linear detail ensure that Elsa will be comfortable and welcomed in any bathroom.

Standard flow rate is 2.5gpm for handshower only. Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS





ELSA ELXT52

Elsa Exposed Tub Filler with Metal Cross Handles and Handshower and Metal Lever Diverter

