

BOULEVARD

Boulevard One Hole Bidet Fitting with Lever Handles

BD01BF



SHOWN IN NICKEL WITH LEVER HANDLES

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 38 mm
Deck Thickness Minimum: 5 mm
Drain Assembly Materials: Brass
Drain Depth Maximum: 44 mm
Drain Style: Pop-up
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 35 mm
Handle Spread Maximum: 133 mm
Handle Spread Minimum: 133 mm
Handle Turn Angle: Quarter Turn
Depth / Width: 102 mm
Drain Depth Minimum: 35 mm
Height: 108 mm
Inlet Connection Size: 3/8"
Inlet Connection Type: 10mm O.D. Supply Tube
Length: 191 mm
Number of Handles: Two
Number of Holes: One Hole
Pivot: N
Primary Material: Brass
Spout Swivel: Y
Suggested Application: Bath
Valve Material: Ceramic
Water Pressure Maximum: 5.5 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

Drawing inspiration from found objects of the 1930's, Boulevard evokes a spirit of extravagance, exuding a strong silhouette, lavish scale, and elegant decoration. The crisp detail and repeated curves require both machine and the artisan hands.

CODES & STANDARDS

Code # : Certified with IAPMO & State of MA. Compliant with ASME A112.18.1/CSA B125.1, ASME A112.18.2/CSA B125.2, ANSI A117.1 ADA & ASTM E 1621-05

PRODUCT FEATURES

Brass metal is used for all trim and valve components.

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Solidly sized and generous in scale, decorative elements convey a sense of substance.

BD01BF