## LUDLOW

## LDXT70

Ludlow Floor Mounted Exposed Tub Filler with Handshower and Metal Lever Handles



SHOWN IN LUDLOW FLOOR MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND METAL LEVER HANDLES | LDXT70

#### **INSPIRATION**

A touch of classic Americana. Our fresh take on iconic industrial design has clean lines and dimensional details.

#### TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed Spray Depth/Width: 10 7/8" Diameter Of Head: 2 1/16" Diameter Of Legs Tubes: 1 7/16" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 68" Height: 38 1/8" Inlet Connection Size: 3/4" Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Freestanding Integrated Diverter: N Integrated Spray: N Length: 16 15/16" Number Of Handles: Two Number Of Holes: Two Hole Pivot: N Primary Material: Brass Spout Swivel: N Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

#### **CODES & STANDARDS**

Complies with ASME A112.18.1/CSA B125.1, cUPC, and ADA. Certified with IAPMO, CEC, State of MA, and WRAS.

**PRODUCT FEATURES** 

Handshower is easy and comfortable to grip.

This item is stocked in a Chrome, Nickel and Unlacquered Brass finishes.

Includes floor unions

Diverter button allows bather to move water from spout to handshower

Stocked in 2.5gpm (7.6 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details

CERTIFICATIONS



### PRODUCT (NOTES)

# LUDLOW

Ludlow Floor Mounted Exposed Tub Filler with Handshower and Metal Lever Handles

## LDXT70