

HENRY

HN20SH

Henry Gooseneck Wall Mounted 7 7/8" Shower Rose, Arm and Flange



SHOWN IN HENRY GOOSENECK WALL MOUNTED 8" SHOWER ROSE, ARM AND FLANGE| HNSH2o

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Diameter of Head: 200 mm
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 25 mm
Flow Restriction Options: 2.0, 1.5
Depth / Width: 603 mm
Height: 535 mm
Inlet Connection Size: 3/4"
Inlet Connection Type: Male G/BSPP
Installation Type: Wall Mounted
Integrated Diverter: N
Integrated Spray: N
Length: 200 mm
Pivot: N
Primary Material: Brass
Restricted Maximum Flow Rate: 9.5 liters/min
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath
Water Pressure Maximum: 5.5 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Brass material is used for components.

Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

WATERWORKS

HENRY

HN20SH

Henry Gooseneck Wall Mounted 7 7/8" Shower Rose, Arm and Flange

