.25 PTS201

.25 10" Rain Showerhead with 12" Ceiling Mounted Shower



## **TECHNICAL DETAILS**

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 1 1/4' Flow Restriction Options: 1.5, 1.75, 2.0 Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Pivot: Y Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN .25 10" RAIN SHOWERHEAD WITH 12" CEILING MOUNTED SHOWER ARM | PTS201

#### **INSPIRATION**

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful.

#### **CODES & STANDARDS**

PTS201X, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), WaterSense(1.5GPM, 1.75GPM & 2.0GPM Only), DOE, State of MA

## **PRODUCT FEATURES**

Made of Brass

Features a swivel 10" rain showerhead with easy clean rubber nozzles

Includes a 12" ceiling mounted shower arm

Stocked in Brass, Chrome, Nickel and Matte Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate

## **CERTIFICATIONS**






# PRODUCT (NOTES)

.25 PTS201

.25 10" Rain Showerhead with 12" Ceiling Mounted Shower



STYLE NO.	DIM "A"	DIM "B"
LVS200	10 <sup>5</sup> / <sub>16</sub> " [261mm]	6 <sup>9</sup> / <sub>16</sub> " [167mm]
PTS200		
LVS201	16 <sup>5</sup> / <sub>16</sub> " [414mm]	12 <sup>9</sup> / <sub>16</sub> " [319mm]
PTS201		
LVS202	22 <sup>5</sup> / <sub>16</sub> " [566mm]	18 <sup>9</sup> / <sub>16</sub> " [472mm]
PTS202		

CEILING VIEW SCALE: 3"=1'-0"

