

## UNIVERSAL

Universal Pressure Balance Valve

## GUPB81



SHOWN IN UNIVERSAL PRESSURE BALANCE VALVE | GUPB81

### TECHNICAL DETAILS

ADA Compliance: Yes  
 Control Valve Rough-in Depth Maximum: 2 7/8"  
 Control Valve Rough-in Depth Minimum: 1 7/8"  
 Fittings Hole Diameter: 3 1/2"  
 Depth / Width: 5 3/4"  
 Height: 3 3/4"  
 Inlet Connection Size: 1/2"  
 Inlet Connection Type: Copper Sweat  
 Integrated Diverter: N  
 Length: 4 3/4"  
 Outlet Connection Size: 1/2"  
 Outlet Connection Type: Sweat Shower / Sweat Tub  
 Primary Material: Brass  
 Safety Warnings: The risk of scalding exists until the installer has properly set the temperature high limit stop screw.  
 Suggested Application: Bath  
 Valve Material: Stainless Steel/ Rubber  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

### CODES & STANDARDS

Code # GUSV81: ASME A112.18.1 / CSA B125.1, IAPMO, CSA, State of MA, NSF

### PRODUCT FEATURES

Built in Anti-scald protection.  
 For use with Waterworks Pressure Balance trims  
 4.2 gpm unrestricted maximum flow at 45 psi  
 1/2" sweat inlet and 1/2" sweat shower/NPT tub outlet. The maximum turn of the valve is approximately one revolution. This large adjustment allows for infinite settings to have a comfortable showering temperature.




### PRODUCT (NOTES)

The risk of scalding exists until the installer has properly set the temperature high limit stop screw.


## UNIVERSAL

Universal Pressure Balance Valve


## GUPB81



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"