

## UNIVERSAL

## GUVC18

Universal 1/2" Counter-Clockwise Open Volume Control Valve



SHOWN IN UNIVERSAL 1/2" CLOCKWISE OPEN VOLUME CONTROL VALVE| GUVC19

### TECHNICAL DETAILS

ADA Compliance: Yes  
Fittings Hole Diameter: 1 3/8"  
Handle Turn Angle: Quarter Turn  
Depth / Width: 6 15/16"  
Height: 2 9/16"  
Inlet Connection Size: 1/2"  
Inlet Connection Type: Female NPT  
Length: 1"  
Outlet Connection Size: 1/2"  
Outlet Connection Type: Female NPT  
Primary Material: Brass  
Suggested Application: Bath  
Valve Material: Ceramic  
Water Pressure Maximum: 85.0 psi  
Water Pressure Minimum: 20.0 psi  
Water Pressure Recommended: 45.0 psi

### INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

### CODES & STANDARDS

Code # GUSV18: State of MA, NSF

### PRODUCT FEATURES

Customize your bath experience with a hot cartridge rough, for use with Waterworks Studio wall valve trims  
1/2" NPT female inlet and outlet with quarter turn functionality  
6 gpm unrestricted maximum flow at 45 psi  
Made of brass materials



## UNIVERSAL

## GUVC18

Universal 1/2" Counter-Clockwise Open Volume Control Valve

