

## ISLA

IS2T05

Isla Two Way Diverter Valve Trim for Thermostatic System with Metal Geode Handle



### TECHNICAL DETAILS

Control Valve Rough-in Depth Maximum: 5 3/8"  
Control Valve Rough-in Depth Minimum: 3 1/8"  
Escutcheon Primary Material: Brass  
Fittings Hole Diameter: 2 1/2"  
Handle Turn Angle: Quarter Turn Each Way  
Depth / Width: 3 3/16"  
Height: 4 1/2"  
Length: 4 3/8"  
Suggested Application: Bath

### INSPIRATION

Pure, timeless, unique and versatile - sculptural organic forms meet advanced engineering in this inspiring collection of fittings, hardware and accessories.

### PRODUCT FEATURES

Features faceted Geode Handle

For use with a Thermostatic shower system and two waterway outlets such as a handshower, shower head, or tub spout

Requires the Two Way Diverter Valve Rough with Shutoff: US: GUDV14 and UK: GU14DV


Stocked in Nickel, Unlacquered Brass, Burnished Nickel, and Burnished Brass finishes



## ISLA

## IS2T05

Isla Two Way Diverter Valve Trim for Thermostatic System with Metal Geode Handle




TOP VIEW

SCALE: 3"=1'-0"




ISO VIEW

SCALE: 3"=1'-0"



FRONT VIEW

SCALE: 3"=1'-0"



SIDE VIEW

SCALE: 3"=1'-0"