

BOND

BLS32B

Bond Tandem Series Wall Mounted Lavatory Faucet with Two-Tone Single Lever Handle



SHOWN IN BOND TANDEM SERIES WALL MOUNTED LAVATORY FAUCET WITH TWO-TONE SINGLE LEVER HANDLE | BLS32B

TECHNICAL DETAILS

ADA Compliance: Yes
 Drain Depth Maximum: 2 5/8"
 Drain Depth Minimum: 3/8"
 Drain Hole Diameter: 1 3/4"
 Drain Style: Push Touch
 Fittings Hole Diameter: 1 3/8"
 Handle Turn Angle: Quarter Turn
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Female NPT
 Number Of Holes: Two Hole
 Primary Material: Brass
 Restricted Maximum Flow Rate: 1.2 gpm
 Spout Swivel: N
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

State of MA

PRODUCT FEATURES

Lever Handle

Includes European size push touch drain

Features Two-Tone Handle

Stocked in Nickel and Brass

Available in 1.2gpm (4.5L/min) flow rate; Requires rough valve, sold separately: GULV29

CERTIFICATIONS



PRODUCT (NOTES)

BOND

BLS32B

Bond Tandem Series Wall Mounted Lavatory Faucet with
Two-Tone Single Lever Handle

