

LUDLOW

Ludlow Ceiling Mounted Shower Arm and Flange

LDSH10



SHOWN IN LUDLOW CEILING MOUNTED SHOWER ARM AND FLANGE| LDSH10

TECHNICAL DETAILS

Escutcheon Primary Material: Brass
Fittings Hole Diameter: 25 mm
Depth / Width: 64 mm
Height: 152 mm
Inlet Connection Size: 1/2"
Inlet Connection Type: Male NPT
Installation Type: Ceiling Mounted
Integrated Diverter: N
Integrated Spray: N
Length: 64 mm
Pivot: N
Primary Material: Brass
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath
Water Pressure Maximum: 6.0 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

A touch of classic Americana. Our fresh take on iconic industrial design has clean lines and dimensional details, including exposed screws and square plates.

CODES & STANDARDS

Code # LDSH10Y: Certified with cUPC, NSF, IAPMO, CSA, CEC

PRODUCT FEATURES

Shower arms can be partnered with a variety of shower heads (sold separately) such as the 6" rain head or 4 1/2" shower rose.

This item is stocked in a Chrome, Nickel and Unlacquered Brass finishes.

Customize your shower with a shower arm and flange suited to your space's unique needs.

Shower arms can be partnered with a variety of shower heads (sold separately) such as the 6" rain head or 4 1/2" shower rose.

CERTIFICATIONS



LUDLOW

Ludlow Ceiling Mounted Shower Arm and Flange

LDSH10

