**BOND** BLS34B

Bond Tandem Series Wall Mounted Lavatory Faucet with Two-Tone Guilloche Lines Single Knob Handle



# **TECHNICAL DETAILS**

ADA Compliance: Yes Drain Depth Maximum: 2 5/8" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2 Handle Turn Angle: Quarter Turn Inlet Connection Size: 1/2" Inlet Connection Type: Female NPT Number Of Holes: Two Hole Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

Shown in Bond Tandem Series wall mounted lavatory faucet with two-tone guilloche lines single knob handle  $\mid$  BLS34B

### **INSPIRATION**

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

### **CODES & STANDARDS**

BLS34BX, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

## **PRODUCT FEATURES**

Knob Handle

Includes European size push touch drain

Features Two-Tone Knob Handle

Stocked in Nickel and Brass

Available in 1.2gpm (4.5L/min) flow rate; Requires rough valve, sold separately: GULV29

# CERTIFICATIONS





# PRODUCT (NOTES)

BOND BLS34B

Bond Tandem Series Wall Mounted Lavatory Faucet with Two-Tone Guilloche Lines Single Knob Handle

