Bond BLS72B

Bond Tandem Series Wall Mounted Lavatory Faucet with Two-Tone Lever Handles



### **TECHNICAL DETAILS**

ADA Compliance: Yes Drain Depth Maximum: 67 mm Drain Depth Minimum: 10 mm Drain Hole Diameter: 44 mm Drain Style: Push Touch Fittings Hole Diameter: 35 mm Handle Spread Maximum: 203 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Each Way

Inlet Connection Size: 1/2" Inlet Connection Type: Female NPT Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 4.5 liters/min

Spout Swivel: N

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN BOND TANDEM SERIES WALL MOUNTED LAVATORY FAUCET WITH TWO-TONE LEVER HANDLES | BLS72B

### **INSPIRATION**

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

### **CODES & STANDARDS**

BLS72BX, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, DOE, State of MA

### **PRODUCT FEATURES**

Lever Handles

Includes Universal Push-Touch Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Stocked in Nickel and Brass

Available in 1.2gpm (4.5L/min) flow rate; Requires valve, sold separately: GULV25 (USA) or GU25LV (UK/International)

# CERTIFICATIONS





## PRODUCT (NOTES)

Bond BLS72B

Bond Tandem Series Wall Mounted Lavatory Faucet with Two-Tone Lever Handles

