FA02TF **EASTON**

Easton Classic Low Profile Concealed Tub Filler With Handshower and Metal Lever Handles



SHOWN IN NICKEL WITH WHITE PORCELAIN MARKED INDICE

TECHNICAL DETAILS

ADA Compliance: No

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 38 mm

Deck Thickness Minimum: 0 mm Diameter of Head: 76 mm

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 35 mm

Flow Restriction Options: 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 305 mm Handle Spread Minimum: 254 mm

Handle Turn Angle: Quarter Turn

Handshower / Spray Hose Length: 2.0 m

Index Color / Finish and Material: White Porcelain

Depth / Width: 311 mm

Height: 184 mm

Index Marking: Hot/Cold

Inlet Connection Size: 3/4"

Inlet Connection Type: Male G/BSPP Inlet Supply Spread Maximum: 305 mm

Inlet Supply Spread Minimum: 254 mm

Installation Type: Deck Mounted

Integrated Diverter: N Length: 457 mm

Number of Handles: Two

Number of Holes: Four Hole

Pivot: N

Primary Material: Brass

Restricted Maximum Flow Rate: 9.5 liters/min

Spout Reach: 10"

Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 5.5 bar

Water Pressure Minimum: 1.5 bar

Water Pressure Recommended: 3.0 bar

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods Code # : ASME A112.18.1, CSA B125, ASSE 1014, IAPMO, and a selection of products from fittings to furniture.

CODES & STANDARDS

State of MA

PRODUCT FEATURES

Brass metal is used for all trim and valve components

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Standard flow rate is 2.5gpm for handshower only. Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

EASTON EA02TF

Easton Classic Low Profile Concealed Tub Filler With Handshower and Metal Lever Handles

