

HIGHGATE

Highgate Handshower On Bar

HGHS10



SHOWN IN HIGHGATE HANDSHOWER ON BAR | HGHS10

TECHNICAL DETAILS

ADA Compliance: Yes
 Adjustable Versus Fixed Spray: Fixed Spray
 Depth/Width: 4 3/4"
 Diameter Of Head: 2 3/4"
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 1 1/4"
 Flow Restriction Options: 1.75
 Handshower Spray Hose Length: 59"
 Height: 26 3/8"
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Female NPT
 Installation Type: Wall Mounted
 Integrated Diverter: N
 Pivot: Y
 Primary Material: Brass
 Suggested Application: Bath
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Our take on old English style: simple, functional shapes, detailed with white porcelain indices and hexagonal accents for a timeless feel.

CODES & STANDARDS

HGHS10X, HGHS10X, ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection. CEC, State of MA

PRODUCT FEATURES

Adjustable 24" bar allows for ease in determining the desired height of handshower, with a wheel pivot to make adjustments simple

All finishes available for immediate shipment (subject to availability)

The handshower is easy to grip offering a round spray pattern

Available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

WATERWORKS

HIGHGATE

HGHS10

Highgate Handshower On Bar

