REGULATOR RGHS02

Regulator Handshower on Hook



TECHNICAL DETAILS

ADA Compliance: When installed per ADA guidelines Adjustable Versus Fixed Spray: Fixed

Adjustable Versus Fixed Spray: Fixed Depth/Width: 5 11/16"

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1"

Flow Restriction Options: 2.5, 2.2, 2.0, 1.75, 1.5, 0.92

Handshower Spray Hose Length: 59"

Height: 12 1/8"

Inlet Connection Size: 1/2"

Inlet Connection Type: Female NPT

Length: 2 5/8"

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm

Suggested Application: Bath

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN REGULATOR HANDSHOWER ON HOOK | RGHS02

INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

CODES & STANDARDS

RGHS02-F.RX, ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection. CEC(1.5GPM & 1.75GPM Only), DOE, State of MA

PRODUCT FEATURES

2 3/4" Head

Features a Fixed Spray Pattern

Stocked in Nickel and Brass

Handshower Available in 1.75gpm (6.6L/min) Flow Rate

CERTIFICATIONS





PRODUCT (NOTES)

REGULATOR RGHS02

Regulator Handshower on Hook

