

R.W. ATLAS

RWTH10

R.W. Atlas Thermostatic Control Valve Trim with Metal Lever Handle



SHOWN IN R.W. ATLAS THERMOSTATIC CONTROL VALVE TRIM WITH METAL LEVER HANDLE | RWTH10

TECHNICAL DETAILS

ADA Compliance: Yes
Control Valve Rough-in Depth Maximum: 3 1/4"
Control Valve Rough-in Depth Minimum: 2 1/2"
Diverter Valve Rough-in Depth Maximum: 4 1/8"
Diverter Valve Rough-in Depth Minimum: 3 1/8"
Fittings Hole Diameter: 5 1/4"
Depth / Width: 3 7/8"
Height: 6 5/16"
Integrated Diverter: N
Integrated Spray: N
Length: 6 3/4"
Number of Handles: One
Pivot: N
Primary Material: Brass
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

CODES & STANDARDS

Code # RWTH10: Complies with ASME A112.18.1/CSA B125.1, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC and State of MA.

PRODUCT FEATURES

Features knurled detail on the handle.
Features knurled detail on the handle.
Meets ADA requirements.



PRODUCT (NOTES)

Requires 3/4" Universal Thermostatic Valve: 26-42456-04860.

