HENRY CHRONOS

CXT211

Henry Chronos Deck Mounted Exposed Tub Filler with Handshower and Lever Handles



TECHNICAL DETAILS

ADA Compliance: No

Deck Thickness Maximum: 1 13/16" Deck Thickness Minimum: 1/4" Fittings Hole Diameter: 1 3/8" Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 60"

Inlet Connection Size: 3/4"
Inlet Connection Type: Male NPT and Male BSPP

Inlet Supply Spread Maximum: 8"

Inlet Supply Spread Minimum: 8"
Integrated Diverter: Y

Number Of Holes: Two Hole Pivot: Y

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm

Spout Swivel: N

Spray Included In Unit: Y

Valve Material: Brass and Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY CHRONOS DECK MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND LEVER HANDLES | CXT211

INSPIRATION

Inspired by dive watches, Henry Chronos radiates design prowess and technical precision. Chronos retains the design integrity of our original, iconic Henry collection, while imbuing it with modern details and exquisite materials.

CODES & STANDARDS

CXT211-F.RX, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), WaterSense(1.5GPM, 1.75GPM & 2.0GPM Only), DOE, State of MA

PRODUCT FEATURES

Features All Metal Lever Handles

Diverter Knob Allows Bather to Move Water From Spout to Handshower

Handshower Offers a Fixed Spray Pattern, Handshower Post Can Swivel to Allow User to Position Handshower Over the Tub Stocked in Brass, Chrome and Nickel

 $Unrestricted\ Flow\ for\ Tub\ Spout.\ Handshower\ Available\ in\ 1.75gpm\ (4.5L/min)\ Flow\ Rate$

CERTIFICATIONS





PRODUCT (NOTES)

HENRY CHRONOS

CXT211

Henry Chronos Deck Mounted Exposed Tub Filler with Handshower and Lever Handles

