

## Flyte

FLLS50

Flyte One Hole Lavatory Faucet with Lever Handle



SHOWN IN FLYTE ONE HOLE LAVATORY FAUCET WITH LEVER HANDLE | FLLS50

## INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

## PRODUCT FEATURES

Lever Handle

Includes Universal Push-Touch Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Stocked in Chrome, Nickel, Brass and Matte Black

Available in 1.2gpm (4.5L/min) flow rate

## TECHNICAL DETAILS

ADA Compliance: Yes  
Adjustable Versus Fixed Spray: Fixed Spray  
Deck Thickness Maximum: 97 mm  
Deck Thickness Minimum: 0 mm  
Depth/Width: 194 mm  
Drain Depth Maximum: 51 mm  
Drain Depth Minimum: 32 mm  
Drain Hole Diameter: 38 mm  
Escutcheon Primary Material: Brass  
Fittings Hole Diameter: 35 mm  
Flow Restriction Options: 1.2  
Handle Turn Angle: Half Turn  
Height: 149 mm  
Inlet Connection Size: 3/8"  
Inlet Connection Type: Compression Connector  
Hoses  
Installation Type: Deck Mounted  
Integrated Diverter: N  
Integrated Spray: N  
Length: 387 mm  
Number Of Handles: One  
Number Of Holes: One Hole  
Primary Material: Brass  
Restricted Maximum Flow Rate: 4.5 liters/min  
Spout Swivel: N  
Spray Included In Unit: N  
Suggested Application: Bath  
Valve Material: Ceramic  
Water Pressure Maximum: 6.0 bar  
Water Pressure Minimum: 1.5 bar  
Water Pressure Recommended: 3.0 bar

## CODES &amp; STANDARDS

FLLS50X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

## CERTIFICATIONS



## PRODUCT (NOTES)

## Flyte

FLLS50

Flyte One Hole Lavatory Faucet with Lever Handle

