FORMWORK FMLS30

Formwork Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes Deck Thickness Maximum: 2" Deck Thickness Minimum: 3/8" Depth/Width: 7 1/2" Drain Depth Maximum: 2 5/8" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch

Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Height: 9 1/16"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8"

Length: 13 5/8"

Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN FORMWORK GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES | FMLS30

INSPIRATION

Sculptural forms that defy the ordinary. Unexpected geometry and the transition of the planes create a subtle but warm expression.

CODES & STANDARDS

FMLS30X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372,

PRODUCT FEATURES

Lever Handles

Modern Push-Touch Euro style drain included.

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS

PRODUCT (NOTES)

FORMWORK FMLS30

Formwork Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

