WATERWORKS

BOND BLS34A

Bond Tandem Series Wall Mounted Lavatory Faucet with Guilloche Lines Single Knob Handle



TECHNICAL DETAILS

ADA Compliance: Yes Drain Depth Maximum: 2 5/8" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2 Handle Turn Angle: Quarter Turn Inlet Connection Size: 1/2" Inlet Connection Type: Female NPT Number Of Holes: Two Hole Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

BLS34AX, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Knob Handle

Includes European size push touch drain

Features Linear Guilloche Etching Knob Handle

Stocked in Nickel and Brass

Available in 1.2gpm (4.5L/min) flow rate; Requires rough valve, sold separately: GULV29

CERTIFICATIONS





PRODUCT (NOTES)

BOND BLS34A

Bond Tandem Series Wall Mounted Lavatory Faucet with Guilloche Lines Single Knob Handle

