### HENRY

## HNXT70

Henry Exposed Floor Mounted Tub Filler with Handshower and Metal Lever Handles



SHOWN IN HENRY EXPOSED FLOOR MOUNTED TUB FILLER WITH HANDSHOWER AND METAL LEVER HANDLES | HNXT70

#### **INSPIRATION**

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

#### **TECHNICAL DETAILS**

ADA Compliance: No Adjustable Versus Fixed Spray: Fixed Spray Depth/Width: 10 13/16" Diameter Of Head: 1 7/8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8" Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 59" Height: 42 1/16" Inlet Connection Size: 3/4" Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Freestanding Integrated Diverter: N Integrated Spray: N Number Of Handles: Two Number Of Holes: Two Hole Primary Material: Brass Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

#### **CODES & STANDARDS**

ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection. CEC

#### **PRODUCT FEATURES**

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Brass material is used for components.

Includes floor unions

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details

CERTIFICATIONS

### PRODUCT (NOTES)

# HENRY

### HNXT70

Henry Exposed Floor Mounted Tub Filler with Handshower and Metal Lever Handles

