WATERWORKS

R.W. ATLAS RWTS01

R.W. Atlas Wall Mounted Tub Spout



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable Versus Fixed Spray: Fixed Spray Depth/Width: 9 1/4" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1" Height: 2 13/16" Inlet Connection Size: 3/4" Inlet Connection Type: Female NPT Installation Type: Wall Mounted Integrated Diverter: N Integrated Spray: N Length: 2 13/16 Number Of Holes: One Hole Pivot: N Primary Material: Brass Spout Swivel: N Spray Included In Unit: N Suggested Application: Bath Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN R.W. ATLAS WALL MOUNTED TUB SPOUT | RWTS01

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

CODES & STANDARDS

ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Features knurled detail on the spout.

Unrestricted flow rate is 13 gpm at 45 psi.

CERTIFICATIONS



PRODUCT (NOTES)

R.W. ATLAS RWTS01

R.W. Atlas Wall Mounted Tub Spout

