WATERWORKS

ASTORIA ATXT10

Astoria Exposed Tub Filler With Handshower and Cross Handles



TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray

Diameter of Head: 2"

Escutcheon Primary Material: Brass

Flow Restriction Options: 2.5, 2.2, 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 5 7/8" Handle Spread Minimum: 5 7/8"

Depth / Width: 6" Height: 12 1/2"

Inlet Connection Size: 3/4"

Inlet Connection Type: Supply Nut

Inlet Supply Spread Maximum: 5 7/8"

Inlet Supply Spread Minimum: 5 7/8"

Integrated Diverter: Y

Length: 10" Pivot: N

Primary Material: Brass

Spout Swivel: N

Suggested Application: Bath

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN ASTORIA EXPOSED TUB FILLER WITH HANDSHOWER AND CROSS HANDLES ATXT10

INSPIRATION

Astoria is dignified tradition. Firmly grounded in the 1930's, the design is an eclectic mix of distinctive geometric profiles, generous scale, and elegant design.

CODES & STANDARDS

Code # JUTU10: ASME A112.18.1, CSA B125, IAPMO, State of MA

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

The signature hexagonal lever draws inspiration from the linear sophistication of the 1930's.

 $\label{lem:comprehensive} A \ comprehensive \ product \ line \ of \ fittings \ options \ for \ the \ lavatory, \ shower, \ and \ bathtub.$

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.









ASTORIA ATXT10

Astoria Exposed Tub Filler With Handshower and Cross Handles

