

LUDLOW

Ludlow Wall Mounted Tub Spout

LD8oTS



SHOWN IN LUDLOW WALL MOUNTED TUB SPOUT| LDTS8o

TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 25 mm
Depth / Width: 202 mm
Height: 76 mm
Inlet Connection Size: 1/2"
Inlet Connection Type: Male G/BSPP
Installation Type: Wall Mounted
Integrated Diverter: N
Integrated Spray: N
Length: 64 mm
Number of Holes: One Hole
Pivot: N
Primary Material: Brass
Spout Reach: 7 3/8"
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath
Water Pressure Maximum: 5.5 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

A touch of classic Americana. Our fresh take on iconic industrial design has clean lines and dimensional details, including exposed screws and square plates.

CODES & STANDARDS

Code # LD8oTS: Certified with cUPC, NSF, IAPMO, CSA and WRAS.

PRODUCT FEATURES

Works seamlessly with Waterworks' thermostatic or diverter shower systems.

This item is stocked in a Chrome, Nickel and Unlacquered Brass finishes.

Unrestricted flow of approximately 12 gallons per minute (gpm)

CERTIFICATIONS



LUDLOW

Ludlow Wall Mounted Tub Spout

LD8oTS

