

## AMELIE

## AM10TF

Amelie High Profile Concealed Tub Filler with Handshower and Metal Lever Handles



SHOWN IN NICKEL WITH LEVER HANDLES

### TECHNICAL DETAILS

ADA Compliance: No  
 Adjustable versus Fixed Spray: Fixed Spray  
 Deck Thickness Maximum: 38 mm  
 Deck Thickness Minimum: 0 mm  
 Diameter of Head: 76 mm  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 35 mm  
 Handle Spread Maximum: 305 mm  
 Handle Spread Minimum: 254 mm  
 Handle Turn Angle: Quarter Turn  
 Handshower / Spray Hose Length: 2.0 m  
 Index Color / Finish and Material: White Porcelain  
 Depth / Width: 292 mm  
 Height: 254 mm  
 Index Marking: Hot/Cold  
 Inlet Connection Size: 3/4"  
 Inlet Connection Type: Male BSP  
 Inlet Supply Spread Maximum: 305 mm  
 Inlet Supply Spread Minimum: 254 mm  
 Installation Type: Deck Mounted  
 Integrated Diverter: N  
 Length: 438 mm  
 Number of Handles: Two  
 Number of Holes: Four Hole  
 Pivot: N  
 Primary Material: Brass  
 Restricted Maximum Flow Rate: 9.5 liters/min  
 Spout Swivel: N  
 Suggested Application: Bath  
 Valve Material: Ceramic  
 Water Pressure Maximum: 5.5 bar  
 Water Pressure Minimum: 1.5 bar  
 Water Pressure Recommended: 3.0 bar

### INSPIRATION

The ultimate in decorative, luxurious fittings with no apologies for its lack of restraint. Amelie offers curves, moldings and detailing combined to create an over-the-top effect which is luxurious, Old World and elegant.

### PRODUCT FEATURES

Brass material is used for all trim and valve component parts. The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

### CODES & STANDARDS

Code # : ASME A112.18.1, ASSE 1014, IAPMO, State of MA

# WATERWORKS

## AMELIE

## AM10TF

Amelie High Profile Concealed Tub Filler with Handshower and Metal Lever Handles

