


HENRY CHRONOS

CKM611

Henry Chronos Double Gooseneck Integrated Pull Spray Kitchen Faucet with Lever Handles



SHOWN IN HENRY CHRONOS DOUBLE GOOSENECK INTEGRATED PULL SPRAY KITCHEN FAUCET WITH LEVER HANDLES | CKM611

TECHNICAL DETAILS

ADA Compliance: Yes
 Adjustable Versus Fixed Spray: Adjustable Spray
 Deck Thickness Maximum: 2 3/4"
 Fittings Hole Diameter: 1 1/2"
 Handshower Spray Hose Length: 59"
 Inlet Connection Size: 3/8"
 Inlet Connection Type: Compression Connection Hoses
 Restricted Maximum Flow Rate: 1.75 gpm
 Spout Swivel: Y
 Spray Included In Unit: Y
 Valve Material: Brass and Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Inspired by dive watches, Henry Chronos radiates design prowess and technical precision. Chronos retains the design integrity of our original, iconic Henry collection, while imbuing it with modern details and exquisite materials.

CODES & STANDARDS

CKM611X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1

PRODUCT FEATURES

Features Lever Handles

Stocked in Chrome, Nickel, and Brass

Available in 1.75 gpm (6.6 L/min) flow rate

Features thermostatic temperature control, desired temperature can be preset by using the center wheel handle while top lever diverts water between either spout

Pull-down sprayhead with dual function, allows the use to switch between aerated stream and jet spray

CERTIFICATIONS



PRODUCT (NOTES)

