

.25

PTW004

.25 Push-Touch Waste and Overflow Drain



SHOWN IN .25 PUSH-TOUCH WASTE AND OVERFLOW DRAIN| PTW004

## TECHNICAL DETAILS

Drain Assembly Materials: Brass  
 Drain Depth Maximum: 46 mm  
 Drain Hole Diameter: 51 mm  
 Drain Style: Push-Touch  
 Escutcheon Primary Material: Brass  
 Installation Notes: All final connections are made below the finished floor. Accessibility below the finished floor is recommended. For installations that have access from below the finished floor, trap adapters can be used instead of the slip joint gasket supplied. For installations where access from below the finished floor is limited, i.e. slabs; the slip joint gasket supplied is required. Refer to the Installation Guidelines for further details.  
 Depth / Width: 254 mm  
 Drain Depth Minimum: 41 mm  
 Height: 254 mm  
 Length: 73 mm  
 Outlet Connection Size: 1 1/2"  
 Outlet Connection Type: Tailpiece  
 Overflow Depth Maximum: 33 mm  
 Overflow Depth Minimum: 3 mm  
 Overflow Hole Diameter: 51 mm  
 Primary Material: Brass  
 Suggested Application: Bath

## INSPIRATION

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful.

## CODES & STANDARDS

Code # WWDR04: ASME A112.18.2 / CSA B125.2, IAPMO, State of MA

## PRODUCT FEATURES

Brass material used for all trim and valve component parts.  
 The manufacturing process includes casting, turning, forging, hand fitting and hand polishing  
 Uses a simple pop-up drain that is closed and opened by pushing down on the stopper. Does not use a lift rod to operate the drain stopper.

## CERTIFICATIONS




.25

PTW004


.25 Push-Touch Waste and Overflow Drain



TOP VIEW SCALE: 1 1/2"=1'-0"



FRONT VIEW SCALE: 1 1/2"=1'-0"



SIDE VIEW SCALE: 1 1/2"=1'-0"