

Regulator

RGXT20

Regulator Exposed Wall Mounted Tub Filler with Handshower and Two-Tone Wheel Handles



SHOWN IN REGULATOR EXPOSED WALL MOUNTED TUB FILLER WITH HANDSHOWER AND TWO-TONE WHEEL HANDLES | RGXT20

INSPIRATION

With striking scale and unique design, Regulator commands attention through its tribute to early 20th-century boiler room controls, when pride was lavished on hard-built parts. Each handcrafted fitting brings dramatic beauty through powerful proportions and honest details.

PRODUCT FEATURES

Two-Tone Wheel Handle

Handshower Offers a Fixed Spray Pattern

Stocked in Nickel/Matte Black and Brass/Matte Black

Unrestricted Flow for Tub Spout. Handshower Available in 1.75gpm (4.5L/min) Flow Rate

TECHNICAL DETAILS

ADA Compliance: No
Adjustable Versus Fixed Spray: Fixed
Depth/Width: 300 mm
Fittings Hole Diameter: 35 mm
Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92
Handle Turn Angle: Quarter Turn
Handshower Spray Hose Length: 1.5 m
Height: 305 mm
Inlet Connection Size: 3/4"
Inlet Connection Type: Compression
Inlet Supply Spread Maximum: 203 mm
Inlet Supply Spread Minimum: 203 mm
Integrated Diverter: Y
Integrated Spray: Y
Length: 314 mm
Primary Material: Brass
Restricted Maximum Flow Rate: 6.6 liters/min
Suggested Application: Bath
Water Pressure Maximum: 6.0 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

CODES & STANDARDS

RGXT20-F.RX, ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection. CEC, State of MA, NOM-012

CERTIFICATIONS



PRODUCT (NOTES)

Regulator

RGXT20

Regulator Exposed Wall Mounted Tub Filler with Handshower and Two-Tone Wheel Handles

