.25 PTLS06

.25 Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 7 1/2"

Drain Assembly Materials: Brass Drain Depth Maximum: 1 3/4" Drain Depth Minimum: 1 1/4" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch

Escutcheon Primary Material: Brass

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Height: 2 1/2"

Inlet Connection Size: 1/2" Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8"

Installation Type: Wall Mounted Length: 10 3/8"

Number Of Handles: Two Number Of Holes: Three Hole Primary Material: Brass Spout Swivel: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN .25 LOW PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES | PTLS06

INSPIRATION

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful.

CODES & STANDARDS

PTLS06X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Uses a simple pop-up drain that is closed and opened by pushing down on the stopper. Does not use a lift rod to operate the drain stopper.

Generous length of the lever handle completes itself with an eased, pillowed square form.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS



PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

.25 PTLS06

.25 Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Lever Handles

