

ETOILE

ETXT60

Etoile Exposed Tub Filler With Handshower and Cross Handles



SHOWN IN ETOILE EXPOSED TUB FILLER WITH HANDSHOWER AND CROSS HANDLES | ETXT60

TECHNICAL DETAILS

ADA Compliance: No
 Adjustable Versus Fixed Spray: Fixed Spray
 Depth/Width: 8"
 Diameter Of Head: 2 1/2"
 Escutcheon Primary Material: Brass
 Handle Spread Maximum: 5.91"
 Handle Spread Minimum: 5.91"
 Handle Turn Angle: Quarter Turn
 Handshower Spray Hose Length: 59"
 Height: 11"
 Index Color Finish And Material: White Porcelain
 Index Marking: Hot/Cold
 Inlet Connection Size: 3/4"
 Inlet Connection Type: Supply Nut
 Inlet Supply Spread Maximum: 5 15/16"
 Inlet Supply Spread Minimum: 5 15/16"
 Installation Type: Wall or deck mounted
 Integrated Diverter: Y
 Length: 8"
 Number Of Handles: Three
 Pivot: N
 Primary Material: Brass
 Restricted Maximum Flow Rate: 2.5 gpm
 Spout Swivel: N
 Suggested Application: Bath
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Defined elegance. Etoile has a European sophistication with a timeless sense of chic.

CODES & STANDARDS

Code # ETTU60: Certified with IAPMO, State of MA & City of LA. Complies with ASME A112.18.1/CSA B125.1, ANSI A117.1 ADA, & ASTM E 1621-05.

PRODUCT FEATURES

Metal cross handles and white porcelain lever diverter

Diverter handle allows bather to move water from spout to handshower with a 2 1/2" head and adjustable spray

Requires unions, sold separately: UNUN32 (Floor Union), ETUN10/ETUN90 (Deck Union) and ETUN04 (Wall Union)

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

Unrestricted flow for tub spout. Stocked in 2.5gpm (9.5L/min) flow rate for handshower.

CERTIFICATIONS

Requires wall unions (ETUN04), deck unions (ETUN10/ETUN90) or unions (UNUN32)

ETOILE

ETXT60

Etoile Exposed Tub Filler With Handshower and Cross
Handles

