

VIAWORKS

GUTH60

ViaWorks 1/2" Thermostatic Valve



SHOWN IN VIAWORKS 1/2" THERMOSTATIC VALVE | GUTH60

TECHNICAL DETAILS

ADA Compliance: When installed per ADA guidelines
 Fittings Hole Diameter: 2 1/2"
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Male NPT
 Outlet Connection Size: 1/2"
 Outlet Connection Type: Male NPT
 Primary Material: Brass
 Valve Material: Wax Element
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

The ViaWorks collection encompasses all Waterworks valves, which are just as impeccably engineered as our legendary fittings and the finest the industry has to offer in terms of performance, features and functionality. ViaWorks valves are engineered with more than three generations of bath and kitchen expertise, each with installers and lifelong service in mind.

CODES & STANDARDS

ASME A112.18.1/CSA B125.1, Complies with ASSE 1016/ASME A112.1016/CSA B125.16, State of MA

PRODUCT FEATURES

- Integrated anti-scald protection.
- 1/2" NPT Connections, color and engraved marking to identify hot and cold water connections
- 6 gpm (gallons per minute) unrestricted maximum flow at 60 psi
- Flows water to up to two shower components simultaneously
- Made in Europe of Brass Construction

CERTIFICATIONS



PRODUCT (NOTES)

VIAWORKS

GUTH60

ViaWorks 1/2" Thermostatic Valve

