DASH DSXT70

Dash Floor Mounted Exposed Tub Filler with Metal Handshower and Lever Handles



SHOWN IN DASH FLOOR MOUNTED EXPOSED TUB FILLER WITH METAL HANDSHOWER AND LEVER HANDLES | DSXT70

### **TECHNICAL DETAILS**

ADA Compliance: No

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 10 11/16" Diameter Of Head: 2 3/8" Diameter Of Legs Tubes: 1 9/16" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8"

Flow Restriction Options: 2.5, 2.2, 2.0, 1.75, 1.5, 1.2, 0.92

Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 59"

Height: 39 15/16"

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Freestanding Integrated Diverter: Y

Integrated Diverter: Y
Integrated Spray: N
Length: 17 1/16"
Number Of Handles: Two

Number Of Holes: Two Hole

Pivot: Y

Primary Material: Brass Spout Swivel: N Spray Included In Unit: Y Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

### **INSPIRATION**

A blend of art and function, Dash pays homage to design elements of the 1930s with pared-down shapes, softened curves and minimal details.

# **CODES & STANDARDS**

State of MA

### PRODUCT FEATURES

Metal Lever Handle

Includes Required Unions for Mounting

 $Hand shower\ hook\ features\ adjust ability\ to\ pivot\ the\ hand shower\ forwards\ or\ backwards$ 

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

# **CERTIFICATIONS**

## PRODUCT (NOTES)

DASH DSXT70

Dash Floor Mounted Exposed Tub Filler with Metal Handshower and Lever Handles

