

CANTEEN

CEKM15

Canteen One Hole High Profile Bar Faucet With Oak Lever Handle



SHOWN IN CANTEEN ONE HOLE HIGH PROFILE BAR FAUCET WITH OAK LEVER HANDLE | CCKM15

TECHNICAL DETAILS

Deck Thickness Maximum: 2 1/4"
 Deck Thickness Minimum: 1/4"
 Depth/Width: 11 1/16"
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 1 3/8"
 Flow Restriction Options: 2.0, 1.75, 1.5
 Handle Turn Angle: Quarter Turn Each Way
 Height: 11 1/16"
 Inlet Connection Size: 3/8"
 Inlet Connection Type: Compression Connector Hoses
 Installation Type: Deck Mounted
 Integrated Diverter: N
 Length: 2 3/4"
 Number Of Holes: Two Hole
 Primary Material: Brass
 Restricted Maximum Flow Rate: 2.2 gpm
 Spout Swivel: Y
 Spray Included In Unit: N
 Suggested Application: Bar, Kitchen, Laundry
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

The traditional kitchen faucet, elevated into a luxurious, heavy-built product. Inspired by the clean simplicity of vintage water pumps, Canteen is sized for drama, with a tall, industrial-elegant spout and durable, handcrafted oak levers. This original, innovative silhouette brings character and dimension to a kitchen.

CODES & STANDARDS

NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, CEC, State of MA

PRODUCT FEATURES

Inspired by the clean simplicity of vintage water pumps.

Features a tall, industrial-elegant spout and durable, handcrafted oak levers.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in high efficiency flow options. Contact a sales associate for details.

CERTIFICATIONS

PRODUCT (NOTES)

CANTEEN

CEKM15

Canteen One Hole High Profile Bar Faucet With Oak Lever Handle

