Bond

BLS720

Bond Solo Series Wall Mounted Lavatory Faucet with Straight Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes Drain Depth Maximum: 67 mm Drain Depth Minimum: 10 mm Drain Hole Diameter: 44 mm Drain Style: Push Touch Fittings Hole Diameter: 35 mm Handle Spread Maximum: 203 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Each Way Inlet Connection Size: 1/2" Inlet Connection Type: Female NPT Number Of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 4.5 liters/min Spout Swivel: N Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN BOND SOLO SERIES WALL MOUNTED LAVATORY FAUCET WITH STRAIGHT LEVER HANDLES | BLS720

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

BLS720X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, DOE, State of MA

PRODUCT FEATURES

Lever Handles

Includes Universal Push-Touch Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Stocked in Chrome, Nickel, Brass and Dark Nickel

Available in 1.2gpm (4.5L/min) flow rate; Requires valve, sold separately: GULV25 (USA) or GU25LV (UK/International)

CERTIFICATIONS



PRODUCT (NOTES)

Bond

BLS720

Bond Solo Series Wall Mounted Lavatory Faucet with Straight Lever Handles

