

## Canteen

CEKM15

Canteen One Hole High Profile Bar Faucet With Oak Lever Handle



SHOWN IN CANTEEN ONE HOLE HIGH PROFILE BAR FAUCET WITH OAK LEVER HANDLE | CCKM15

### TECHNICAL DETAILS

Deck Thickness Maximum: 57 mm  
 Deck Thickness Minimum: 6 mm  
 Depth/Width: 281 mm  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 35 mm  
 Flow Restriction Options: 2.0, 1.75, 1.5  
 Handle Turn Angle: Quarter Turn Each Way  
 Height: 281 mm  
 Inlet Connection Size: 3/8"  
 Inlet Connection Type: Compression Connector  
 Hoses  
 Installation Type: Deck Mounted  
 Integrated Diverter: N  
 Length: 70 mm  
 Number Of Holes: Two Hole  
 Primary Material: Brass  
 Restricted Maximum Flow Rate: 8.3 liters/min  
 Spout Swivel: Y  
 Spray Included In Unit: N  
 Suggested Application: Bar, Kitchen, Laundry  
 Valve Material: Ceramic  
 Water Pressure Maximum: 6.0 bar  
 Water Pressure Minimum: 1.5 bar  
 Water Pressure Recommended: 3.0 bar

### INSPIRATION

Inspired by the clean simplicity of vintage water pumps, Canteen is sized for drama but designed for life. The tall industrial-elegant spout and durable handcrafted oak levers transform a kitchen or bar in timeless, distinctive ways.

### CODES & STANDARDS

NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, CEC, State of MA

### PRODUCT FEATURES

Inspired by the clean simplicity of vintage water pumps.

Features a tall, industrial-elegant spout and durable, handcrafted oak levers.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in high efficiency flow options. Contact a sales associate for details.

### CERTIFICATIONS

### PRODUCT (NOTES)

Canteen

CEKM15

Canteen One Hole High Profile Bar Faucet With Oak Lever Handle

