HENRY HNXS30

Henry Exposed Thermostatic Shower System with 8" Shower Head and Metal Lever and Cross Handle



## **TECHNICAL DETAILS**

ADA Compliance: Yes Adjustable Versus Fixed Spray: Fixed Spray Diameter Of Head: 7 3/4" Diameter Of Legs Tubes: 1 1/8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8" Flow Restriction Options: 2.5, 2.0, 1.75, 1.5 Handle Spread Maximum: 5 11/16' Handle Spread Minimum: 5 11/16" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 59" Inlet Connection Size: 3/4" Inlet Connection Type: Copper Compression Inlet Supply Spread Maximum: 11 5/8" Inlet Supply Spread Minimum: 11 1/8" Installation Type: Wall Mounted

Instalation Type: Wall Mounted
Integrated Diverter: N
Integrated Spray: N
Number Of Handles: Two
Number Of Holes: Two Hole
Pivot: Y
Primary Material: Brass
Suggested Application: Bath
Valve Material: Wax Element
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY EXPOSED THERMOSTATIC SHOWER SYSTEM WITH 8" SHOWER HEAD AND METAL LEVER AND CROSS HANDLE | HNXS30

INSPIRATION CODES & STANDARDS

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CEC

## PRODUCT FEATURES

Available Late Spring 2018

Features an intergrated thermostatic shut-off valve

The Shower Riser is designed to be field cut to accommodate varying shower heights. The exposed diverter body can be installed with the handshower elbow on the right or the left.

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

## CERTIFICATIONS

## PRODUCT (NOTES)

HENRY HNXS30

Henry Exposed Thermostatic Shower System with 8" Shower Head and Metal Lever and Cross Handle

