BOULEVARD BDS167

Boulevard 6" Showerhead with 12" Wall Mounted 90 Degree Shower Arm



### **TECHNICAL DETAILS**

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 1.5, 1.75, 2.0 Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Pivot: Y Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN BOULEVARD 6" SHOWERHEAD WITH 12" WALL MOUNTED 90 DEGREE SHOWER ARM | BDS167

#### **INSPIRATION**

Inspiration from 1930s objects evokes extravagance: a strong silhouette, lavish scale and elegant decoration. Machine and artisan hands yield crisp details and curves.

#### **CODES & STANDARDS**

BDS167X, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), WaterSense(1.5GPM, 1.75GPM & 2.0GPM Only), DOE, State of MA

#### **PRODUCT FEATURES**

Made of Brass

Features a swivel 6" showerhead with easy clean rubber nozzles

Includes a 12" wall mounted 90 degree shower arm

Stocked in Brass, Chrome, Nickel and Matte Nickel

Showerhead available in 1.75gpm (6.6L/min) flow rate

## CERTIFICATIONS





# PRODUCT (NOTES)

BOULEVARD BDS167

Boulevard 6" Showerhead with 12" Wall Mounted 90 Degree Shower Arm

