

## Henry

HNXS50

Henry Exposed Thermostatic Shower System with 8" Shower Head, Handshower, Metal Lever Diverter Handle and Metal Cross Handles



SHOWN IN HENRY EXPOSED THERMOSTATIC SHOWER SYSTEM WITH 8" SHOWER HEAD, HANDSHOWER, METAL LEVER DIVERTER HANDLE AND METAL CROSS HANDLES | HNXS50

## INSPIRATION

Celebrating the connection of industry and art, Henry transitions effortlessly between modern, traditional, and classic settings. These iconic fittings blend 19th-century industrial and artistic references for a look that's forever of the moment—familiar yet wholly original.

## PRODUCT FEATURES

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings

Features an integrated thermostatic shut-off valve

The Shower Riser is designed to be field cut to accommodate varying shower heights. The exposed diverter body can be installed with the handshower elbow on the right or the left.

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 1.75gpm (6.6L/min)

## TECHNICAL DETAILS

ADA Compliance: Yes  
Adjustable Versus Fixed Spray: Fixed Spray  
Diameter Of Head: 197 mm  
Diameter Of Legs Tubes: 29 mm  
Escutcheon Primary Material: Brass  
Fittings Hole Diameter: 29 mm  
Handle Spread Maximum: 144 mm  
Handle Spread Minimum: 144 mm  
Handle Turn Angle: Quarter Turn  
Handshower Spray Hose Length: 1.5 m  
Inlet Connection Size: 3/4"  
Inlet Connection Type: Copper Compression  
Inlet Supply Spread Maximum: 295 mm  
Inlet Supply Spread Minimum: 283 mm  
Installation Type: Wall Mounted  
Integrated Diverter: Y  
Integrated Spray: N  
Number Of Handles: Three  
Number Of Holes: Two Hole  
Pivot: Y  
Primary Material: Brass  
Spray Included In Unit: Y  
Suggested Application: Bath  
Valve Material: Wax Element  
Water Pressure Maximum: 6.0 bar  
Water Pressure Minimum: 1.5 bar  
Water Pressure Recommended: 3.0 bar

## CODES &amp; STANDARDS

CEC

## CERTIFICATIONS

## PRODUCT (NOTES)

