LUDLOW LDXT50

Ludlow Deck Mounted Exposed Tub Filler with Handshower and Lever Handles



SHOWN IN LUDLOW DECK MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND LEVER HANDLES | LDXT50

ADA Compliance: No

Adjustable Versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 2" Deck Thickness Minimum: 3/8" Depth/Width: 10 3/16" Diameter Of Head: 2 1/16" Diameter Of Legs Tubes: 1 7/16" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 1.5, 1.75, 2.0 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 68" Height: 12 11/16" Inlet Connection Size: 3/4" Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Length: 16 15/16" Number Of Handles: Two Number Of Holes: Two Hole Pivot: N Primary Material: Brass Spout Świvel: N Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi

INSPIRATION

Our fresh take on American industrial design comes in two styles, both of them clean-lined and distinct to Waterworks.

CODES & STANDARDS

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

LDXT50X, ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection, CEC, DOE, State of MA

PRODUCT FEATURES

Features All Metal Lever Handles

Diverter handle allows bather to move water from spout to handshower

The Handshower offers a fixed spray pattern

Stocked in Chrome, Nickel and Brass

Unrestricted flow for tub spout. Handshower available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS





PRODUCT (NOTES)

LUDLOW LDXT50

Ludlow Deck Mounted Exposed Tub Filler with Handshower and Lever Handles

