

HIGHGATE

Highgate Exposed Thermostatic System with 6" Shower Rose with White Porcelain Lever Handles

HG7oXS



SHOWN IN CHROME WITH WHITE PORCELAIN HANDLE

TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray
Diameter of Head: 152 mm
Depth / Width: 622 mm
Height: 1151 mm
Inlet Connection Size: 1/2"
Inlet Connection Type: Male G/BSPP
Inlet Supply Spread Maximum: 140 mm
Inlet Supply Spread Minimum: 140 mm
Installation Type: Wall Mounted
Length: 189 mm
Primary Material: Brass
Suggested Application: Bath
Valve Material: Wax Element
Water Pressure Maximum: 5.5 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

Our take on old English style: simple, functional shapes, detailed with white porcelain indices and hexagonal accents for a timeless feel.

PRODUCT FEATURES

Built in Anti-scald protection.

All finishes available for immediate shipment (subject to availability)

Features a 6" swivel shower rose

Add a handshower to this exposed system. Handshower not included.

Standard flow rate 2.0gpm (7.6 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

HIGHGATE

HG7oXS

Highgate Exposed Thermostatic System with 6" Shower Rose
with White Porcelain Lever Handles

