BOND

BLS490

Bond Solo Series One Hole Lavatory Faucet with Straight Lever Handle



TECHNICAL DETAILS

ADA Compliance: Yes Deck Thickness Maximum: 1 13/16" Deck Thickness Minimum: 1/4" Drain Depth Maximum: 2 5/8" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2 Handle Turn Angle: Quarter Turn Inlet Connection Size: 3/8" Inlet Connection Type: Compression Connection Hoses Number Of Holes: One Hole Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm Spout Swivel: Y Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN BOND SOLO SERIES ONE HOLE LAVATORY FAUCET WITH STRAIGHT LEVER HANDLE | BLS490

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

BLS490X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Lever Handle

Includes Universal Push-Touch Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Stocked in Chrome, Nickel, Brass and Dark Nickel

Available in 1.2gpm (4.5L/min) flow rate





PRODUCT (NOTES)

BOND

BLS490

Bond Solo Series One Hole Lavatory Faucet with Straight Lever Handle

