

FLYTE

FLVC50

Flyte Volume Control with Lever Handle



SHOWN IN FLYTE VOLUME CONTROL WITH LEVER HANDLE | FLVC50

TECHNICAL DETAILS

ADA Compliance: Yes
Depth/Width: 2 5/16"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 3/8"
Height: 4 5/16"
Integrated Diverter: N
Integrated Spray: N
Length: 2 3/8"
Number Of Handles: One
Pivot: N
Primary Material: Brass
Spout Swivel: N
Spray Included In Unit: N
Suggested Application: Bath

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

ASME A112.18.1/CSA B125.1, State of MA

PRODUCT FEATURES

Lever Handles

Used to Control Water Flow to a Single Waterway Outlet

Stocked in Chrome, Nickel, Brass and Matte Black

Requires rough valve, Sold separately: GUV18/GUVC19 or GUVC16/GUVC17

CERTIFICATIONS



PRODUCT (NOTES)

Required 1/2" valve rough Hot -GUV18 or Cold -GUVC19, sold separately.


FLYTE

FLVC50


Flyte Volume Control with Lever Handle



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"