FLYTE FLTS90

Flyte Floor Mounted Tub Spout



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable Versus Fixed Spray: Fixed Spray Depth/Width: 12 3/8" Diameter Of Legs Tubes: 1 3/16" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Height: 30 3/8" Inlet Connection Size: 3/4" Inlet Connection Type: Copper Sweat Installation Type: Freestanding Integrated Diverter: N Integrated Spray: N Length: 3 9/16" Number Of Holes: One Hole Pivot: N Primary Material: Brass Spout Swivel: N Spray Included In Unit: N Suggested Application: Bath Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

SHOWN IN FLYTE FLOOR MOUNTED TUB SPOUT | FLTS90

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Floor Mounted

This item is stocked in a Chrome, Nickel, Brass and Matte Nickel

Unrestricted flow

CERTIFICATIONS



PRODUCT (NOTES)

FLYTE FLTS90

Flyte Floor Mounted Tub Spout

