EASTON EALS50

Easton Classic Low Profile Three Hole Wall Mounted Lavatory Faucet with Elongated Spout and Oak Lever Handles



SHOWN IN EASTON CLASSIC LOW PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH ELONGATED SPOUT AND OAK LEVER HANDLES | EALS50

## **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

# **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Drain Assembly Materials: Brass Drain Depth Maximum: 2 3/4" Drain Depth Minimum: 1" Drain Hole Diameter: 1 3/4" Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Index Color Finish And Material: White Porcelain

Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Wall Mounted Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

## **CODES & STANDARDS**

EALS50X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, DOE, State of MA

## PRODUCT FEATURES

Available in 1.2gpm (4.5L/min) flow rate

## CERTIFICATIONS





# PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

EASTON EALS50

Easton Classic Low Profile Three Hole Wall Mounted Lavatory Faucet with Elongated Spout and Oak Lever Handles

