WATERWORKS

UNIVERSAL UNTS34

Universal Wall Mounted Tub Spout



TECHNICAL DETAILS

Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Escutcheon Primary Material: Brass Fittings Hole Diameter: 32 mm Installation Notes: Comes with 1/2inch Female NPT Adapter Depth / Width: 195 mm Height: 64 mm Inlet Connection Size: 3/4" Inlet Connection Type: Female NPT Installation Type: Wall Mounted Length: 64 mm Primary Material: Brass Spout Reach: 7.1" Spout Swivel: N Suggested Application: Bath Water Pressure Maximum: 6.0 bar

SHOWN IN UNIVERSAL WALL MOUNTED TUB SPOUT| UNTS34

INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

CODES & STANDARDS

Code # WWTU34: ASME A112.18.1 / CSA B125.1, IAPMO, State of MA

PRODUCT FEATURES

Create a refined environment for your daily ritual by installing an exquisitely proportioned

A clean, universal aesthetic is applicable to all bath environments (traditional to modern)

A wall mounted tub spout works seamlessly with Waterworks' thermostatic or diverter shower systems

CERTIFICATIONS





UNIVERSAL UNTS34

Universal Wall Mounted Tub Spout

